

The Fairbanks Company

202 Division Street • P.O. Box 1871 • Rome, GA 30162

Toll Free: 800-831-0022 • **Fax:** 800-576-2239

Email: info@fairbankscasters.com • **Web Address:** www.fairbankcaster.com

Steel Lever Dolly

APPLICATION

Lever dollies are best used in pairs to lift each end of heavy machinery, crates or pallets so a moving dolly or forklift can be slid underneath. The new S-72-PO, all steel, heavy-duty lever pry bar dolly is completely USA manufactured. The lever dolly is an all-welded construction using heavy carbon steel. There are no cast metal parts or bolts. The 72" long handle is 1-3/4" OD x 1/8" wall steel tubing. The 3-1/2" long reverse beveled nose point and the handle back brace are made of 5/8" x 6" steel plate. The 5" x 2" polyurethane mold-on cast iron wheels roll easily on the 1-3/16" diameter axle. The lever dolly has an overall lifting height of 9" with a maximum load capacity of 6,500 lbs. The wheel base dimension is 11-1/2" W. x 10-1/2" DP. The finish is polyester powder coated green for protection and durability. Ship weight is 48 lbs.



Item #

Handle Length

Wheel Size

Load Capacity

S-72-PO

72 Inch

5 Inch x 2 Inch

6,500 lbs